## NSN 5962-01-179-8656

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-179-8656
Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
0.085 inches
Maximum Power Dissipation Rating:
105.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
7 input
Design Function And Quantity:
6 flip-flop, d-type, clocked
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-7.0 volts power source
Time Rating Per Chacteristic:
5.30 nanoseconds delay
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 flat leads
Specification Data:
81349-mil-m-38510/61 government specification
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5962-01-179-8656

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0