NSN 5962-01-180-3445

Linear Microcircuit - Page 1 of 1



2-01-180-3445

View Online at https://aerobasegroup.com/nsn/5962-0
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
570.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and high impedance and low bias
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-99 joint electron device engineering council
T0-99 joint electron device engineering council Terminal Surface Treatment:
Terminal Surface Treatment:
Terminal Surface Treatment: Solder
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 8 pin
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 8 pin Shelf Life:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 8 pin Shelf Life: N/a
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 8 pin Shelf Life: N/a

Fiig:

A458a0