

View Online at <https://aerobasegroup.com/nsn/5962-01-180-3466>

Body Length:

Between 0.745 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.310 inches

Body Height:

Between 0.115 inches and 0.140 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and high speed and w/clock and w/common enable and positive edge triggered

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

4 register, d-type

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

12.00 nanoseconds propagation delay time, low to high level output and 17.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0