NSN 5962-01-180-4307

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-180-4307

Dedut Longithe	
Body Length:	
0.960 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
0.185 inches	
Maximum Power Dissipation Rating:	
794.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Programmable and programmed and bipolar	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
12 input	
Case Outline Source And Designator:	
D-6 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
7.0 volts power source	
Time Rating Per Chacteristic:	
85.00 nanoseconds propagation delay time, low to high level output and 85.00 nanoseconds propagation delay time, high to low level	
output	
Memory Device Type:	
Rom	
Memory Capacity:	
Unknown	
Test Data Document:	
35012-102044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Terminal Type And Quantity:	
18 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	

Unit Of Measure:

NSN 5962-01-180-4307

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

