## NSN 5962-01-181-0263

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-181-0263 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5815-01-062-8194 communications terminal **Features Provided:** Low power and schottky and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 1 counter **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 45.00 nanoseconds propagation delay time, low to high level output and 52.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 80063-sm-a-915707 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## **NSN 5962-01-181-0263**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0