## NSN 5962-01-181-1742

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-181-1742

| Body Outside Diameter:   |
|--|
| Between 0.350 inches and 0.370 inches  |
| Body Height:   |
| Between 0.240 inches and 0.260 inches  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -62.0/+125.0 degrees celsius   |
| End Application:   |
| 5840-01-147-7235 radio frequency jammer  |
| Features Provided:   |
| Cascadable and thin film and hermetically sealed   |
| Inclosure Material:  |
| Metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 1 input  |
| Design Function And Quantity:  |
| 1 amplifier, general purpose   |
| Case Outline Source And Designator:  |
| T0-39 joint electron device engineering council  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 5.0 volts power source   |
| Test Data Document:  |
| 72314-1500mc1005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                    |
| Terminal Type And Quantity:  |
| 3 pin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |