## NSN 5962-01-182-3594

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-182-3594

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
330.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 comparator, voltage
Case Outline Source And Designator:
A-1 mil-m-38510
Current Rating Per Characteristic:
50.00 milliamperes forward current, peak total value not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
30.0 volts power source
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin
Specification Data:
81349-mil-m-38510/103 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## NSN 5962-01-182-3594

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0