# NSN 5962-01-182-3594

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-182-3594

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

## Maximum Power Dissipation Rating:

330.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs

#### Inclosure Material:

Metal

Inclosure Configuration:

#### Can

Input Circuit Pattern:

2 input

#### **Design Function And Quantity:**

1 comparator, voltage

Case Outline Source And Designator:

A-1 mil-m-38510

#### Current Rating Per Characteristic:

50.00 milliamperes forward current, peak total value not applicable

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

30.0 volts power source

# **Nuclear Hardness Critical Feature:**

Hardened

#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

8 pin

#### **Specification Data:**

81349-mil-m-38510/103 government specification

### Shelf Life:

N/a

### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# NSN 5962-01-182-3594

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

