NSN 5962-01-183-6569

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-183-6569

View Online at https://aerobasegroup.com/nsn/5962-01-183-6569
Body Length:
Between 0.355 inches and 0.400 inches
Body Width:
Between 0.245 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
1.05 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Teletypewriter set an/ugc-136ax
Features Provided:
Monolithic and high voltage and high current and medium speed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
2 driver, peripheral
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
65.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
00724-72-00975 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-183-6569

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0