## NSN 5962-01-185-5709

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-185-5709 **Body Length:** 0.770 inches **Body Width:** 0.250 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 10.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/schmitt trigger and complementary outputs and w/resistor and positive outputs **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 multivibrator, monostable **Case Outline Source And Designator:** To-116 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 70.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface silver **Precious Material:** Silver **Terminal Type And Quantity:** 14 printed circuit

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5962-01-185-5709

Digital Microcircuit - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A458a0