NSN 5962-01-186-5716

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-186-5716

| Body Length: | |
|--|--|
| 1.290 inches | |
| Body Width: | |
| Between 0.500 inches and 0.610 inches | |
| Body Height: | |
| 0.210 inches | |
| Maximum Power Dissipation Rating: | |
| 1.02 watts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| End Application: | |
| Radar system an/fps-117 | |
| Features Provided: | |
| Hermetically sealed and monolithic and bipolar a | and programmable and schottky |
| Inclosure Material: | |
| Ceramic and glass | |
| Inclosure Configuration: | |
| Dual-in-line | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 14 input | |
| Case Outline Source And Designator: | |
| D-3 mil-m-38510 | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| 5.5 volts power source | |
| Time Rating Per Chacteristic: | |
| 100.00 nanoseconds propagation delay time, lo | ow to high level output and 100.00 nanoseconds propagation delay time, high to low level |
| output | |
| Memory Device Type: | |
| Rom | |
| Memory Capacity: | |
| Unknown | |
| Terminal Type And Quantity: | |
| 24 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |

NSN 5962-01-186-5716

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

