## NSN 5962-01-188-2933

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-188-2933

view Offilite at https://aerobasegroup.com/hist//0302-01-100-2333
Body Length:
0.960 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and static operation
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
D-6 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.3 volts power source
Memory Device Type:
Ram
Memory Capacity:
Unknown
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
18 printed circuit
Specification Data:
81349-mil-m-38510/245 government specification
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5962-01-188-2933

Memory Microcircuit - Page 2 of 2



## Demilitarization:

Yes - demil/mli

Fiig:

A458a0