

View Online at <https://aerobasegroup.com/nsn/5962-01-188-2934>

Body Length:

2.096 inches

Body Width:

Between 0.510 inches and 0.620 inches

Body Height:

Between 0.165 inches and 0.210 inches

Maximum Power Dissipation Rating:

1.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and w/clock and w/reset and burn in

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

1 microprocessor

Case Outline Source And Designator:

D-5 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

40 printed circuit

Specification Data:

81349-mil-m-38510/480 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

A458a0