NSN 5962-01-189-5321

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-189-5321

Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Features Provided:
High voltage and monolithic and dielectric isolated and positive outputs
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Octal 1 input
Design Function And Quantity:
8 driver, display
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
· · · · · · · · · · · · · · · · · · ·
35.0 volts power source
35.0 volts power source
35.0 volts power source Terminal Type And Quantity:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:
35.0 volts power source Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: