

View Online at <https://aerobasegroup.com/nsn/5962-01-189-9485>

Body Outside Diameter:

0.370 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-25.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

4920-01-111-2981 automatic test; virginia class cg (41); oliver perry class ffg; austin ship class lpd-4 amphibious transport docks; forrestal class cv; spruance class dd (963); nimitz class cvn; ticonderoga class cg (47); arleigh burke class ddg; kidd class ddg; support equipment, b-1 aircraft

Features Provided:

Low noise and hermetically sealed

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

T0-99 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

22.0 volts power source

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0