## NSN 5962-01-189-9489

Linear Microcircuit - Page 1 of 1

**Demilitarization:** Yes - demil/mli

**Fiig:** A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-189-9489 **Body Length:** 0.780 inches **Body Width:** Between 0.240 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.180 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Indicator, activity ip-1140/wlr-8 **Features Provided:** Hermetically sealed and high speed and w/resistor and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 4 switch, current **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 40.0 volts power source **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**