# NSN 5962-01-189-9489

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-189-9489

## **Body Length:**

0.780 inches

## Body Width:

Between 0.240 inches and 0.310 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Indicator, activity ip-1140/wlr-8

### **Features Provided:**

Hermetically sealed and high speed and w/resistor and monolithic

#### Inclosure Material:

Ceramic

### Inclosure Configuration:

Dual-in-line

#### **Input Circuit Pattern:**

5 input

## **Design Function And Quantity:**

4 switch, current

## **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

40.0 volts power source

### **Time Rating Per Chacteristic:**

40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0