NSN 5962-01-191-4422

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-191-4422

| Body Length: | |
|---------------------|---|
| 0.625 inches | |
| Body Width: | |
| 0.625 inches | |
| Body Height: | |
| 0.140 inches | |
| | Dissipation Rating: |
| 24.0 watts | sissipation rading. |
| Operating Tempu | rature Range. |
| -55.0/+100.0 degre | - |
| Storage Tempura | |
| -65.0/+150.0 degre | |
| End Application: | |
| 6620-01-048-2889 | indicator, tempe |
| Features Provide | |
| | and monolithic and hybrid |
| Inclosure Materia | |
| Metal | |
| Inclosure Configu | ration: |
| Flat pack | |
| Input Circuit Patte | ern: |
| Dual 1 input | |
| Design Function | And Quantity: |
| 3 triac | |
| Terminal Surface | Treatment: |
| Solder | |
| Precious Material | And Location: |
| Case surface gold | |
| Precious Material | |
| Gold | |
| Test Data Docum | ent: |
| 88818-a574a322 d | rawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any | specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type An | d Quantity: |
| 12 flat leads | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |