

View Online at <https://aerobasegroup.com/nsn/5962-01-191-5774>

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

66.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/alq-161

Features Provided:

Low power and monolithic and schottky and 3-state output and hermetically sealed

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

8 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 multiplexer

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Mircrocircuit, digital, low powerschottky, 8-input multiplexer with 3-state outputs, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

59.00 nanoseconds propagation delay time, high to low level output and 59.00 nanoseconds propagation delay time, low to high level output

Special Features:

Electrostatic discharge sens

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0