NSN 5962-01-192-0184

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-192-0184

View Online at https://aerobasegroup.com/nsn/5962-01-192-0184
Body Length:
Between 1.010 inches and 1.050 inches
Body Width:
Between 0.250 inches and 0.290 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
369.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
4920-01-111-2981 automatic test
Features Provided:
W/enable and high speed and fast settling and positive outputs
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
15 input
Design Function And Quantity:
1 converter, digital to analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Time Rating Per Chacteristic:
160.00 nanoseconds propagation delay time, low to high level output and 160.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
80009-156-1555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Fiig: A458a0

Yes - demil/mli