## NSN 5962-01-193-6038

Digital Microcircuit - Page 1 of 1

**Demilitarization:** Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-193-6038 **Body Length:** 0.350 inches **Body Width:** 0.265 inches **Body Height:** Between 0.050 inches and 0.080 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/totem pole output and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 wide 2-3 input **Design Function And Quantity:** 2 gate, and-or invert **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**