## NSN 5962-01-193-6702

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-193-6702 **Body Length:** 0.400 inches **Body Width:** 0.285 inches **Body Height:** 0.085 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Features Provided:** Hermetically sealed and electrostatic sensitive and monolithic and programmable and positive outputs and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Current Rating Per Characteristic:** 130.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Capitance Rating Per Characteristic:** Between 10.00 input picofarads and 12.00 output picofarads **Time Rating Per Chacteristic:** 45.00 nanoseconds delay **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0