## NSN 5962-01-194-1723

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-194-1723 **Body Length:** 1.300 inches **Body Width:** 0.800 inches **Body Height:** 0.160 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Receiving set, countermeasures an/wlg- (v) **Features Provided:** Hermetically sealed and burn in and hybrid and high performance and bipolar **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 12 input **Design Function And Quantity:** 1 converter, digital to analog **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0