NSN 5962-01-195-1245

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-195-1245

| View Offline at https://defobasegroup.com/hsh/0302-01-135-1240 |
|---|
| Overall Height: |
| Between 0.325 inches and 0.400 inches |
| Body Length: |
| 1.060 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| Between 0.140 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 297.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Low power and schottky and monolithic and 3-state output |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Design Function And Quantity: |
| 8 gate, buffer |
| Case Outline Source And Designator: |
| D-8 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts total supply |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 20 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 5962-01-195-1245

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0