# NSN 5962-01-195-6172

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-195-6172

# **Body Length:**

Between 0.745 inches and 0.785 inches

# Body Width:

Between 0.240 inches and 0.260 inches

# **Body Height:**

Between 0.105 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

W/reset and hermetically sealed and presettable

#### **Inclosure Material:**

Ceramic

# Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

## Input Circuit Pattern:

8 input

#### **Design Function And Quantity:**

1 counter, up/down

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 20.0 volts power source

## **Time Rating Per Chacteristic:**

500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## Terminal Type And Quantity:

16 printed circuit

## Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0