## NSN 5962-01-195-7528

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-195-7528

| Body Outside Diameter:   |
|--|
| Between 0.335 inches and 0.370 inches  |
| Body Height:   |
| 0.180 inches   |
| Maximum Power Dissipation Rating:  |
| 1.8 watts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and burn in and w/current limiter and positive outputs   |
| Inclosure Material:  |
| Metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 2 input  |
| Design Function And Quantity:  |
| 1 regulator, voltage   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 40.0 volts power source  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 10 pin   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |