NSN 5962-01-198-6358

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-198-6358

Overall Height:
0.400 inches
Overall Width:
0.320 inches
Body Length:
0.785 inches
Body Width:
0.310 inches
Body Height:
0.210 inches
Maximum Power Dissipation Rating:
550.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Receiving set, countermeasures an/alr-56c
Features Provided:
Monolithic and high frequency and high slew rate
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
1 channel and 2 input
Design Function And Quantity:
1 amplifier, operational, ultra high frequency
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-12.0 volts power source and 12.0 volts power source
Test Data Document:
81413-231936 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5962-01-198-6358

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0