# NSN 5962-01-198-7117

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-198-7117

# **Body Length:**

Between 0.370 inches and 0.425 inches

# **Body Width:**

Between 0.245 inches and 0.285 inches

# **Body Height:**

Between 0.045 inches and 0.085 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and burn in

#### **Inclosure Material:**

Ceramic

Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Quad 2 input

**Design Function And Quantity:** 

4 transceiver

**Terminal Surface Treatment:** 

Solder

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

# **Time Rating Per Chacteristic:**

18.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level output

# **Test Data Document:**

94117-313088 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

16 flat leads

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# Fiig:

A458a0