NSN 5962-01-198-8899

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-108-8800

| View Online at https://aerobasegroup.com/nsn/5962-01-198-8899 |
|--|
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.180 inches and 0.210 inches |
| Maximum Power Dissipation Rating: |
| 600.0 milliwatts |
| Operating Tempurature Range: |
| -25.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Bipolar and externally compensated and hermetically sealed and high precision and high stability and high gain and low noise and laser |
| trimmed |
| Inclosure Material: |
| Metal and glass |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 1 channel and 3 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 20.0 volts power source |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |