# NSN 5962-01-199-0056

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-199-0056

# **Body Length:**

Between 0.490 inches and 0.520 inches

# **Body Width:**

Between 0.245 inches and 0.285 inches

# **Body Height:**

Between 0.045 inches and 0.085 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Low power and schottky and 3-state output

#### Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

# **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

10 input

#### **Design Function And Quantity:**

1 register, shift, parallel out and 1 register, storage

# **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### **Time Rating Per Chacteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

94117-314017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

20 flat leads

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0