NSN 5962-01-199-0059

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-199-0059

Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.295 inches
Body Height:
0.180 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and cascadable and expandable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
11 input
11 input Design Function And Quantity:
Design Function And Quantity:
Design Function And Quantity: 1 comparator, magnitude
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment:
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document:
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity:
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 printed circuit
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 printed circuit Shelf Life:
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 comparator, magnitude Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure:

A458a0