# NSN 5962-01-199-1622

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-199-1622

# **Body Length:**

0.390 inches

# Body Width:

Between 0.235 inches and 0.260 inches

# **Body Height:**

Between 0.045 inches and 0.085 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Quad 2 input

# **Design Function And Quantity:**

4 gate, or

# **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## **Time Rating Per Chacteristic:**

7.50 nanoseconds propagation delay time, low to high level output and 7.50 nanoseconds propagation delay time, high to low level output

## Test Data Document:

94117-310491 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

14 printed circuit Shelf Life: N/a Unit Of Measure:

---

#### **Demilitarization:**

Yes - demil/mli

# Fiig:

A458a0