NSN 5962-01-199-2561

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-199-2561

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
W/resistor and hermetically sealed and burn in and electrostatic sensitive
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 1 channel and dual 1 input
Design Function And Quantity:
2 driver, switch, field effect transistor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Time Rating Per Chacteristic:
250.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
1 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0