NSN 5962-01-200-1365

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-200-1365

| Body Length: |
|---|
| 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| Dual 4 input |
| Design Function And Quantity: |
| 2 amplifier, operational, general purpose |
| Case Outline Source And Designator: |
| D-1 mil-m-38510 |
| Terminal Surface Treatment: |
| Tin |
| Voltage Rating And Type Per Characteristic: |
| -18.0 volts power source and 18.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0