NSN 5962-01-200-4134

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-200-4134

| Body Length: |
|---|
| Between 1.565 inches and 1.585 inches |
| Body Width: |
| Between 1.065 inches and 1.085 inches |
| Body Height: |
| Between 0.320 inches and 0.380 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -0.0/+65.0 degrees celsius |
| Storage Tempurature Range: |
| -62.0/+75.0 degrees celsius |
| Features Provided: |
| Hybrid and hermetically sealed |
| Inclosure Material: |
| Ceramic or glass or metal |
| Inclosure Configuration: |
| Quad-in-line |
| Input Circuit Pattern: |
| 1 input |
| Design Function And Quantity: |
| 1 amplifier, log |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 13.5 volts power source |
| Special Features: |
| Input power 0.0 dbm max; center frequency 29.0 mhz min and 31.0 mhz max |
| Test Data Document: |
| 10001-2937649 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 15 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |
| Yes - demil/mli |
| 100 WOLLINGTON |

Fiig:

A458a0