

View Online at <https://aerobasegroup.com/nsn/5962-01-200-6584>

Body Length:

0.785 inches

Body Width:

0.291 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and 3-state output and w/enable and high speed

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

8 input

Design Function And Quantity:

6 buffer, tri-state

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 7.5 volts power source

Time Rating Per Characteristic:

280.00 nanoseconds propagation delay time, low to high level output and 280.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0