NSN 5962-01-200-7672

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-200-7672 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 728.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 1520-01-106-9519 helicopter, atta **Features Provided:** Hermetically sealed and burn in and w/switch and electrostatic sensitive and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input and 4 channel **Design Function And Quantity:** 1 multiplexer, differential **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 40.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0