### NSN 5962-01-200-8145

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-200-8145

## Body Length:

0.785 inches

#### Body Width:

Between 0.220 inches and 0.310 inches

#### **Body Height:**

Between 0.140 inches and 0.180 inches

#### Maximum Power Dissipation Rating:

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

High speed and low power

#### **Inclosure Material:**

#### Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

Hex 1 input

#### **Design Function And Quantity:**

6 inverter, digital

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

#### **Time Rating Per Chacteristic:**

13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level output

#### **Special Features:**

Ttl compatible

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# **NSN 5962-01-200-8145** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

