

View Online at <https://aerobasegroup.com/nsn/5962-01-201-2468>

Body Length:

0.785 inches

Body Width:

0.280 inches

Body Height:

0.180 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/slq-32 countermeasure set. Forrestal class cv, spruance class dd (963), nimitz class cvn, kidd class ddg, arleigh burke class ddg, ticonderoga class cg (47). B-1 aircraft support equipment. An/wsc-6 shf satcom radio.

Features Provided:

W/open collector and hermetically sealed and w/strobe

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Criticality Code Justification:

Feat

Design Function And Quantity:

2 decoder, two to four line

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Special Features:

Weapon system essential

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0