## NSN 5962-01-202-2950

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-202-2950 **Body Length:** Between 0.745 inches and 0.785 inches **Body Width:** Between 0.240 inches and 0.310 inches **Body Height:** Between 0.115 inches and 0.140 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -65.0/+165.0 degrees celsius **Features Provided:** W/enable and hermetically sealed and 3-state output and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 4 receiver, line differential

25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

**Time Rating Per Chacteristic:** 

**Test Data Document:**57230-es48ttl-26ls32 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

57230-es48ttl-26ls32 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0