NSN 5962-01-202-2960

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-202-2960 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 739.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and programmable and bipolar and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

N/a

Unit Of Measure:

16 printed circuit

Shelf Life:

Terminal Type And Quantity:

NSN 5962-01-202-2960

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0