NSN 5962-01-202-4197

Digital Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-202-4197 **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.150 inches and 0.195 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and schottky and w/buffered output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Case Outline Source And Designator:** D-3 mil-m-38510 **Time Rating Per Chacteristic:** 100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 18876-13032789 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli