

View Online at <https://aerobasegroup.com/nsn/5962-01-202-8622>

**Body Length:**

Between 0.750 inches and 0.785 inches

**Body Width:**

Between 0.240 inches and 0.295 inches

**Body Height:**

0.180 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-55.0/+150.0 degrees celsius

**Features Provided:**

Buffered reset and burn in and electrostatic sensitive and hermetically sealed and high fan-out and high impedance and monolithic and positive edge triggered and static operation and w/buffered output and w/common clock and w/reset and 2-state output

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

8 stage and 6 input

**Design Function And Quantity:**

2 shift register, static

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

18.0 volts power source

**Time Rating Per Characteristic:**

750.00 nanoseconds propagation delay time, low to high level output and 750.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0