NSN 5962-01-203-1276

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-203-1276

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Retriggerable and resettable and low power
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 multivibrator, monostable
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Time Rating Per Chacteristic:
600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig: