NSN 5962-01-203-1278

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-203-1278

Body liends: José Dichoss and 0.310 inches Body Widt: Between 0.220 inches and 0.310 inches Body Widts: Body Widts: Body Might: José Dichos and 0.310 inches Body Might: José Dichos And Dichos And Dichos Body Might: José Dichos And Dichos And Dichos And Dichos Body Body Might: José Dichos And Dichos And Dichos And Dichos Body Body Might: José Dichos And Dichos And Dichos And Dichos Body Body And Dichos And Dichos And Dichos And Dichos Body Body Body Body Body Body Body Body	
Body With: Bedyeen 0.220 inches and 0.310 inches Body Height: 10.185 inches Body millivatis 50.00 millivatis Operating Tempurature Range: -50.01 125.0 degrees celsius Body and the range: -50.01 125.0 degrees celsius End Application: Sinulator m-9854b/u Pactare Provided: Bipolar and monthitic and fast settling Bipolar and monthitis and fast settling Bipolar and monthitis and fast settling Dual-in-line Output Logic Forn: Transistor-transistor logic Houtput 10 input Polage Rand monthiti 10 andu 10 input 10 andu 10 andu <td></td>	
Bear Bioles Outsinches Maximum Power Dissipation Rating: 500.0 millivatts Operating Tempurature Range: -550.0 125.0 degrees celsius Storage Tempurature Range: -650.0 to 150.0 degrees celsius Storage Tempurature Range: -650.0 to 150.0 degrees celsius Biograft Tempurature Range: -650.0 to 50.0 degrees celsius Biograft Tempurature Range: Biograft Tempurature Range: Biograft Tempurature Range: Biograft Tempurature Range: Datatin-fine Datatin-fine Datatin-fine Datatin-fine Datatin-fine Datatin-fine Datatin-fine Datatio-fraction And Quantity: I converter, digital to analog Tempuration for Comment:	
Body Height: 0.185 inches Maximum Power Dissipation Rating: 500.0 milliwatis Operating Tempurature Range: 650.10 120.0 degrees celsius Storage Tempurature Range: 650.10 120.0 degrees celsius Parating Tempurature Range: 650.10 120.0 degrees celsius Endage Tempurature Range: 650.10 120.0 degrees celsius Parating Tempurature Range: 180.0 and monolithic and fast settling Biolara monolithic and fast settling Biolara monolithic and fast settling 180.0 and monolithic and fast settling Tearsitor Configuration: 10 aduin-line Output Logic Form: 17 Tansistor Lagic Form: 18 and Rating And Quantity: 19 anput 10 anput Degree Rating And Type Per Characteristic: 18 angle And Type Per Characteristic: 18 angle And Type And Quantity: 19 aprile And Bast andard (includes industry or association standards, individual manufactureer standards, etcl. 19 aprile And Bast and Tage Set Algo Algo Algo Algo Algo Algo Algo Algo	-
145 inches 5030 millivatis 5000 millivatis 5010 millivatis 6300 afgress celsius 6300 afgress celsius 6400 affacto afgress celsius Factor Application: 1010 affacto affa	
Aximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -50.0 125.0 degrees celsius Storage Tempurature Range: -63.0 to 150.0 degrees celsius Bindatom: Simulator mx-9854b/u Features Provided: Biolar and monellihic and fast settling Inclosure Material: Coramic Holdspie Dual-In-line Output Logic Form: Transistor-transistor logic Hordspie Output Logic Form: 1 converter, digital to analog Terminal Surface Treatment: 1 converter, digital to analog Postage Rating And Type Per Characteristic: 1 soulds: power source Postage Rating And Type Per Characteristic: 1 sources Postage Rating And Type Per Characteristic: 1 sources Postage Rating And Type Per Characteristic: 1 sources 1 sprinted circuit Postage Rating And Type And Quantity: 1 sprinted circuit Postage Rating And Type	Body Height:
S0.0 millivattsOperating Tempurature Range:-55.0 to 125.0 degrees celsiusStorage Tempurature Range:-65.0 to 150.0 degrees celsiusCand Application:Simulator mx-9854b/uFeatures Provided:Bipolar and monolithic and fast settlingInclosure Material:CoramicHoldspress Configuration:Dual-In-IneDual-In-IneCoramicInsistor-transistor logicInput Cricuit Pattern:10 inputDesign Function And Quantity:1 converter, digital to analogVortage Rating And Type Per Characteristic:18 soluts on solution (includes industry or association standards, individual manufactureer standards, etc.)19 inputStore Instituted (includes industry or association standards, individual manufactureer standards, etc.)10 inputConverter19 input dictute:10 inputDisponser Source10 inputPostal Document:10 input10 input standard (includes industry or association standards, individual manufactureer standards, etc.)10 input standard (includes industry or association standards, individual manufactureer standards, etc.)10 input standard (includes industry or association standards, individual manufactureer standards, etc.)10 input standard (includes industry or association standards, individual manufactureer standards, etc.)10 input standard includes industry or association standards, individual manufactureer standards, etc.)10 input standard10 input standard10 in	0.185 inches
Operating Tempurature Range:-55.0 to 125.0 degrees celsiusStorage Tempurature Range:-65.0 to 150.0 degrees celsiusEnd Application:Simulator mx-9854b/uFeatures Provided:Biolar and monolithic and fast settlingInclosure Material:CeramicDual-in-lineOutput Logic Form:Transistor-transistor logicInput Croute Patterne:10 inputOutput cogic Form:10 autorter, digital to analogPerminal Surface Treatment:Solder <td>Maximum Power Dissipation Rating:</td>	Maximum Power Dissipation Rating:
Scho 125.0 degrees celsius Scho 150.0 degrees celsius End Application: Simulator mx-9854b/u Fetters Provide: Bipolar and monolithic and fast settling Inclosure Material: Ceramic Daul-in-line Output Logic Form: Tansistor-transistor logic Input Crouit Pattern: 10 input Output Logic Form: 10 input Database end and and quantity: 10 converter, digital to analog 20 rest Stodes end and (includes industry or association standards, individual manufactureer standards, etc.) Stoles Stoles 10 fort fortiont 10 source: 10 source: 10 source: 10 source: 10 source: 10 source: 11 source: 12 source: 12 source: 13 source: 14 source: 15 source: 16 source: 17 source: 18 source: 19 source: 19 source: 10	500.0 milliwatts
Storage Tempurature Range: -65.0 to 150.0 degrees celsius End Application: Simulator mx-9854b/u Features Provided: Bipolar and monolithic and fast settling Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Degree Transistor logic Incoverter, digital to analog Terminal Surface Treatment: Solder Votage Rating And Type Per Characteristic: 18.0 volts power source Terminal Type And Quantity: 19.0 spin-tick-des standard (includes industry or association standards, individual manufactureer standards, etc.) Solder Votage Rating And Type Per Characteristic: 18.0 volts power source Terminal Type And Quantity: 19.1 printed circuit Solder Voltage Rating And Type Per Characteristic: 19.1 printed circuit 10.1 for Measure: 10.1 for Measure: 10.1 for Measure: 10.1 for Measure:	Operating Tempurature Range:
- 45.0 to 150.0 degrees celsius End Application: Simulator mx-9854b/u Features Provide: Bipolar and monolithic and fast settling Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: 10 input Distor-transistor logic Intro Circuit Pattern: 10 input Pesign Function And Quantity: 1 converter, digital to analog Perminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18 ovolts power source Terminal Type And Quantity: 1 sprinted circuit Big printed circuit Solder Voltage Rating And Type Per Characteristic: 18 volts power source Terminal Type And Quantity: 18 printed circuit Pathel Life: Na Chof Measure: - Pathel Life: Pathel Life: Fomiliartization: Formiliartization: Formiliartization:	-55.0 to 125.0 degrees celsius
End Application: Simulator mx-9854b/u Features Provided: Bipolar and monolithic and fast settling Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Vatage Rating And Type Per Characteristic: 18.0 volts power source Terminal Type And Quantity: 18.0 volts power source Terminal Type And Quantity: 19.0 volts 10.1	Storage Tempurature Range:
Sinulator mx-9854b/u Features Provided: Bipolar and monolithic and fast settling Inclosure Material: Caramic Caramic Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 11 converter, digital to analog Terminal Surface Treatment: Solder Polata Document: 18:0: volts power source Exercised include includes industry or association standards, individual manufactureer standards, etc.) Pathel file: Nal Solder Interminal Surface Treatment: Solder Polita Document: 18:0 volts power source Exercised Standard (includes industry or association standards, individual manufactureer standards, etc.) Pathel file: Nal Chord Measure: Int of Measure: <t< td=""><td>-65.0 to 150.0 degrees celsius</td></t<>	-65.0 to 150.0 degrees celsius
Features Provided: Bipolar and monolithic and fast settling Icolosure Material: Coramic Caramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-Iransistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Partial Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18:0 volts power source Solder Periant Surface Treatment: 19:0 volts power source Terminal Surface And Unduet industry or association standards, individual manufactureer standards, etc.) 19:0 volts power source 10:0 volts Periant Type And Quantity: 10:1 volta direcut 10:1 volta Via Via <td>End Application:</td>	End Application:
Biplar and monolithic and fast settling Icolosure Material: Ceramic Icolosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Posign Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Fest Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Freminal Type And Quantity: 18 printed circuit Sheff Life: Na Positifier Na Fort I Measure: Vita C Measure: I- Positifier Solder Positifier Na Store Positifier Store Positifier Na Store Positifier Positifier Positifier <	Simulator mx-9854b/u
Iclosure Material: Ceranic Iclosure Configuration: Dual-inine Output Logic Forn: Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Geson-mil-std-s83 standard (includes industry or association standards, individual manufactureer standards, etc.). Ferminal Type And Quantity: 18 printed circuit Sheff Life: Nat Chell Life: Nat Ferminal Type And Quantity: 19 sprinted circuit Sheff Life: Nat Chelliarization: Yes - demil/Inti	Features Provided:
Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Terminal Type And Quantity: 19806-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) Perimenal Type And Quantity: 18 printed circuit Sheff Life: N/a Circuit Patters: Int Of Measure: r remiltarization: Femiltarization: Fig:	Bipolar and monolithic and fast settling
Iclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Terminal Type And Quantity: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) Terminal Type And Quantity: 18 printed circuit Sheff Life: N/a Circuit Patters: Partice Circuit Forminal Type And Quantity: N/a Circuit Patters: N/a Disting Circuit Patters: N/a Circuit Patters: N/a Circuit Patters: Patters: Vita Offenseure: Vita Offenseure: Terminal Type And Quantity: N/a Disting Circuit Patters: Patters: Distance:	Inclosure Material:
Dual-in-lineOutput Logic Form:Transistor-transistor logicInput Circuit Pattern:10 inputDesign Function And Quantity:1 converter, digital to analogTerninal Surface Treatment:SolderVoltage Rating And Type Per Characteristic:18.0 volts power sourceTest Data Document:96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).Terminal Type And Quantity:18 printed circuitNaChell Life:NaFormilarization:r-Femilitarization:Fig:	Ceramic
Output Logic Form:Transistor-transistor logicInput Circuit Pattern:10 inputDesign Function And Quantity:Persign Function And Quantity:1 converter, digital to analogTerminal Surface Treatment:SolderVoltage Rating And Type Per Characteristic:18.0 volts power sourceTest Data Document:69006-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).Terminal Type And Quantity:18 printed circuitShelf Life:N/aUnd Measure:Formiltarization:Yes - demil/mliFig:	Inclosure Configuration:
Transistor-transistor logic Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Dual-in-line
Input Circuit Pattern: 10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: - Pemiltarization: Yes - demi/mli Fig:	Output Logic Form:
10 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 06906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Sheff Life: N/a Life Measure: Fmilitarization: Yes - demil/mii	Transistor-transistor logic
Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: - Pemilitarization: Yes - demil/mil	Input Circuit Pattern:
1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Femilitarization: Yes - demil/mli	10 input
Terminal Surface Treatment:SolderVoltage Rating And Type Per Characteristic:18.0 volts power sourceTest Data Document:09606-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).Perminal Type And Quantity:18 printed circuitShelf Life:N/aUnit Of Measure:Permilitarization:Yes - demil/mliFig:	Design Function And Quantity:
Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Ferminal Type And Quantity: 18 printed circuit Shelf Life: N/a N/a Life: Dim Of Measure: Ferminal Type Interiment Int	1 converter, digital to analog
Voltage Rating And Type Per Characteristic:18.0 volts power sourceTest Data Document:96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).Perminal Type And Quantity:18 printed circuitShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mliFig:	Terminal Surface Treatment:
18.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Solder
Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: - Penilitarization: Yes - demil/mli Fig:	Voltage Rating And Type Per Characteristic:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	18.0 volts power source
Terminal Type And Quantity: 18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Filg:	Test Data Document:
18 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	18 printed circuit
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Demilitarization: Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
-	Yes - demil/mli
A458a0	Fiig:
	A458a0