NSN 5962-01-203-7276



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-203-7276 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** Between 0.265 inches and 0.291 inches **Body Height:** 0.199 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** Computer-display set an/uyq-2 (v) **Features Provided:** High speed and programmable and schottky and w/open collector **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-203-7276

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0