NSN 5962-01-204-1639

Memory Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5962-01-204-1639
Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.271 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Computer-display set an/uyq-2 (v)
Features Provided:
Schottky and programmed and high speed and w/open collector
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low leve
output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-204-1639

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0