NSN 5962-01-205-7413

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-205-7413

view Offiline at https://aerobasegroup.com/hist//3302-01-203-7413
Body Length:
Between 0.740 inches and 0.870 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.204 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive and hermetically sealed and negative outputs and positive outputs
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
1 channel and 5 input
Design Function And Quantity:
1 switch, double pole double throw
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
Δ458a0