NSN 5962-01-206-0586



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-206-0586 **Body Length:** 0.810 inches **Body Width:** 0.300 inches **Body Height:** 0.095 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and high speed and low power **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 converter, digital to analog **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 18.0 volts power source **Time Rating Per Chacteristic:** 100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

Fiig:

A458a0