## NSN 5962-01-206-5878

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-206-5878
Body Length:
Between 0.337 inches and 0.350 inches
Body Width:
Between 0.200 inches and 0.300 inches
Body Height:
Between 0.008 inches and 0.100 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Edge triggered and hermetically sealed and schottky
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 flip-flop, j-k, clocked
Case Outline Source And Designator:
F-2 mil-m-38510
Time Rating Per Chacteristic:
7.00 nanoseconds propagation delay time, low to high level output and 7.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
18876-11437250 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0